IAP2 Rec'd PCT/PTO 29 SEP 2006

# AMENDMENTS IN ACCORDANCE WITH ARTICLE 11

# IAP2 Resud PCT/PTO 29 SEP 2006

### AMENDMENT OF PROCEEDINGS

(Amendment in accordance with Article 11)

To the Patent Examiner, Japan Patent Office

1. International application identification:

PCT/JP2005/005065

2. Applicant

Name: PIONEER CORPORATION

Address: 4-1, Meguro 1-chome, Meguro-ku, Tokyo 153-8654 Japan

Nationality: Japanese

Address: Japan

3. Agent

Name: (7911) FUJIMURA Motohiko

Address: FUJIMURA PATENT BUREAU

Togeki Bldg., 1-1, Tsukiji 4-chome, chuo-ku,

Tokyo 104-0045 Japan

Phone: 03-3545-5555

Fax :03-3545-2898

- 4. Parts amended: Claims
- 5. Content of the amendment
- (1) Claim 1 has been amended from "intensity." to "intensity, wherein the two-dimensional recording layer is disposed between the hologram recording layer and the reflecting layer."
- (2) Claim 4 has been canceled.
- 6. List of attachments
- (1) Claims, pages 33-34

## **CLAIMS**

1. (Amended) A hologram record carrier that has a substrate and a reflecting layer, where recording or reproducing of information is performed by light irradiation, characterized by comprising:

a hologram recording layer that reserves an optical interference pattern comprising components of coherent reference light and signal light as a diffractive grating therein; and

a two-dimensional recording layer that is laminated in a film thickness direction of the hologram recording layer and whose physical property changes in response to light intensity,

wherein the two-dimensional recording layer is disposed between the hologram recording layer and the reflecting layer.

- 2. The hologram record carrier according to claim 1, wherein the optical interference pattern is produced by a first light beam so that a hologram is recorded, and the two-dimensional recording layer senses a second light beam so that a mark is recorded according to change of the physical property.
- 3. The hologram record carrier according to claim 2, wherein the hologram recording layer has a sensitivity to a wavelength of the first light beam higher than that to a wavelength of the second light beam, and the two-dimensional recording layer is a phase-change film, a pigmented coat, or a magneto-optical recording film where a sensitivity to a wavelength of the second light beam is set to be higher than a sensitivity to a wavelength

of the first light beam.

# 4. (Deleted)

- 5. The hologram record carrier according to any one of claims 1 to 4, wherein the two-dimensional recording layer is dispose on a side of a light irradiation face of the holographic recording layer.
- 6. The hologram record carrier according to any one of claims 1 to 5, wherein an end mark indicating an end of the hologram or a group of the holograms recorded on the holographic recording layer is recorded at a portion of the two-dimensional recording layer laminated on a portion of the holographic recording layer recorded with the hologram or the group of the holograms.
- 7. The hologram record carrier according to any one of claims 1 to 5, wherein an address mark indicating an address of the hologram or a group of the holograms recorded on the holographic recording layer is recorded at a portion of the two-dimensional recording layer laminated on a portion of the holographic recording layer recorded with the hologram or the group of the holograms.
- 8. The hologram record carrier according to any one of claims 1 to 5, wherein a relational mark indicating information relating to the hologram or a group of the holograms recorded on the holographic recording layer is recorded at a portion of the